


AX Water Spire 10 bar



Mandrel built suction & delivery hose for water and non corrosive fluids. Suitable for agriculture, industry and public works.

Temperature: -30°C to +80°C

- **Tube:** black smooth SBR/NBR rubber
- **Reinforcement:** high tensile textile plies and embedded steel spiral
- **Cover:** black SBR/EPDM rubber with cloth impression, weather and abrasion resistant

Assembly

all types of industrial couplings and flanges
safety clamps, bandimex, colliers de serrage HD

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Bending radius (mm)	Vacuum (mH2O)	Coil length (m)
RAXWS019	19 x 28	680	10	30	120	0,9	40 - 61
RAXWS025	25 x 34	800	10	30	150	0,9	40 - 61
RAXWS032	32 x 42	980	10	30	190	0,9	40 - 61
RAXWS038	38 x 48	1.200	10	30	230	0,9	40 - 61
RAXWS050	51 x 62	1.790	10	30	300	0,9	40 - 61
RAXWS063	63 x 74	2.150	10	30	380	0,9	40 - 61
RAXWS075	76 x 88	2.800	10	30	460	0,9	40 - 61
RAXWS100	102 x 116	4.200	10	30	600	0,9	40 - 61
RAXWS125	127 x 143	5.900	10	30	750	0,9	40 - 61
RAXWS150	152 x 168	7.850	10	30	900	0,8	40 - 61
RAXWS200	203 x 227	15.200	10	30	1.600	0,8	10
RAXWS250	254 x 282	23.500	10	30	2.000	0,8	10
RAXWS300	305 x 337	30.000	10	30	2.400	0,7	10



Source URL: <https://alfaflex.com/en/products/40000/40900/ax-water-spire-10-bar-0>