


AX Fibreglass 20 bar



Mandrel built glassfibre covered hose resisting to steel splashes.

Temperature: -40°C to +130°C

- **Tube:** black smooth EPDM rubber
- **Reinforcement:** high tensile textile plies
- **Cover:** black EPDM rubber covered with vulcanized glass fibre ply, resistant to radiant heat

Applications

Delivery of water cooling in foundries, glass, steel or iron industry. For situations where hoses are exposed to sprinkles of red hot material.

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Coil length (m)
FBR010	10 x 20	300	20	60	40
FBR013	13 x 24	450	20	60	40
FBR016	16 x 27	500	20	60	40
FBR019	19 x 32	600	20	60	40
FBR025	25 x 39	900	20	60	40
FBR030	30 x 42	800	20	60	40
FBR032	32 x 48	1.300	20	60	40
FBR038	38 x 55	1.700	20	60	40
FBR040	40 x 59	1.900	20	60	40
FBR050	51 x 71	2.500	20	60	40
FBR065	65 x 86	3.250	20	60	40

Product ID: 40940

Source URL: <https://alfaflex.com/en/products/40000/40900/ax-fibreglass-20-bar-0>