

## Filclair N



Flexible and polyvalent reinforced pvc hose; suitable for a large number of media: industrial gasses or liquids. Filclair can be used in vacuüm up to Ø25mm.

Temperature: -15°C to +60°C

- **Tube:** transparant pvc
- **Reinforcement:** high tensile textile thread
- **Cover:** transparant pvc

**Attention:** not suitable for hydrocarbons and derivates

On demand also available in different colours.

### Applications

supply of compressed air for machinery  
industrial gases and liquids  
light chemical products

### Assembly

All types of industrial couplings  
assembly with hose-clamps

Reference	Diameter (mm)	Bending radius (mm)	Weight (g/m)	Working Pressure (bar)	Burst Pressure (bar)	Coil length (m)
FC0408	4 x 8	40	49	10	30	50
FC0508	5 x 8	40	39	10	30	50
FC0611	6,3 x 11	50	82	10	30	50
FC0612	6 x 12	55	110	15	50	50
FC0813	8 x 13	65	105	10	30	50
FC0814	8 x 14	60	130	15	50	50
FC0915	9 x 15	65	141	15	50	50
FC1015	10 x 15	85	131	10	30	50
FC1016	10 x 16	75	155	15	50	50
FC1218	12 x 18	105	170	10	30	50
FC1319	13 x 19	90	192	15	50	50
FC1320	13 x 20	90	225	15	50	50
FC1521*	15 x 21	145	216	10	30	50
FC1622	16 x 22	155	222	10	30	50
FC1926	19 x 26	195	302	10	30	50
FC2533	25 x 33	235	432	10	30	50
FC3242*	32 x 42	185	716	12	38	25 - 50
FC3848*	38 x 48	220	865	10	32	25
FC5060	50 x 60	390	1072	8	24	25



Product ID: 12080

**Source URL:** <https://alfaflex.com/en/products/10000/12000/filclair-n-0>