

Profilair 20 bar



The Profilair air hose is a lightweight pvc hose for medium duty compressed air applications (up to 20 bar).

Temperature: -15°C to +60°C

- **Tube:** black pvc
- **Reinforcement:** high tensile polyester fibre
- **Cover:** beige or black UV resistant pvc

Working pressure and test pressure measured at 23°C.

Applications

Compressed air - Spraying machine - Supply pneumatic machines
Equipment for small material - Passage of industrial gas and air
Various applications

Assembly

Diameter (mm)	Bending radius (mm)	Weight (g/m)	Working Pressure (bar)	Burst Pressure (bar)	Reference Beige	Reference Back	Coil length (m)
6 x 12	50	109	20	63	PA06	PAZ06	50
7 x 13	55	120	20	63	PA07	PAZ07	50
8 x 14	65	130	20	63	PA08	PAZ08	50
9 x 15	70	143	20	63	PA09	PAZ09	50
10 x 16	75	155	20	63	PA10	PAZ10	50
12,7 x 20	90	225	20	63	PA12	PAZ12	50
16 x 24	125	315	20	63	PA16	PAZ16	50
19 x 27	150	363	20	63	PA19	PAZ19	50
25 x 34	195	520	20	63	PA25	PAZ25	50

Product ID: 12110

Source URL: <https://alfaflex.com/en/products/10000/12000/profilair-20-bar-0>