

Alfaril



Temperature: -15°C to +80°C

Alfaril is a mono layered, non reinforced polyamide 12 tube and has an excellent chemical resistance to oils, fats, hydrocarbons, salts, acids, bases. This tube is also resistant to hydrolysis and keeps its characteristics at high humidity levels. It is used in special applications combined under difficult conditions, like chemicals and/or mechanical load.

Main characteristics:

- calibrated following the tolerances in BS5409/1/2
- light (density of 1,01 kg/dm³)
- hardness 61 ± 3° ShA
- very good elasticity
- abrasion resistant
- keeps shape in vacuum
- low friction and low loss of charges
- very good shock resistance

Coil lengths: 25, 50 en 100m

Applications

fuel lines, pneumatic brake lines, transport of gas, chemicals and lubricants.

Diameter (mm)	Bending radius (mm)	Weight (g/m)	WP / BP (bar)	Ref Natural	Ref Blue	Ref Yellow	Ref Green	Ref Red	Ref Black
2 x 4	7,3	25	38/40	T110204	T11B0204	T11G0204	T11GR0204	T11R0204	T11Z0204
2,7 x 4	10,6	30	22/40	T110304	T11B0304	T11G0304	T11GR0304	T11R0304	T11Z0304
4 x 6	16,7	35	23/33	T110406	T11B0406	T11G0406	T11GR0406	T11R0406	T11Z0406
6 x 8	23,7	55	13/33	T110608	T11B0608	T11G0608	T11GR0608	T11R0608	T11Z0608
8 x 10	30	90	17/33	T110800	T11B0810	T11G0810	T11GR0810	T11R0810	T11Z0810
10 x 12	36,6	92	10/30	T111012	T11B1012	T11G1012	T11GR1012	T11R1012	T11Z1012
11 x 14	61	90	16/48	T111114	-	-	-	-	-



13 x 16	72,4	115	12/24	-	-	-	-
				T111316			

Product ID: 12210

Source URL: <https://alfaflex.com/en/products/10000/12000/alfaril-0>