

Opal



PVC hose reinforced by an hard pvc spiral, with food grade quality, suitable for the suction and delivery of a multitube of media and food stuffs. Opal is very easy to handle even at low temperatures.

Temperature: -10°C to +60°C

Construction: transparent pvc with food grade quality with an embedded hard white pvc spiral in the hose wall, smooth inside.

Passage of food products or liquids according to simulants A, B, C, and D1 (approved by the IANESCO testing laboratory Report RE-13/02869 and RE-13/02867)

Reference	Diameter (mm)	Wall thickness (mm)	Weight (g/m)	Bending radius (mm)	Working Pressure (bar)	Vacuum (mH20)	Coil length (m)
NE020	20	2,9	250	100	6	7	25* - 50
NE025	25	2,9	310	135	6	7	25* - 50
NE030	30	3	370	140	6	7	25* - 50
NE032	32	3,1	400	150	6	7	25* - 50
NE035	35	3,2	490	165	6	7	25* - 50
NE038	38	3,4	530	180	6	7	25* - 50
NE040	40	3,6	560	190	6	7	25* - 50
NE045	45	3,8	680	210	5	7	25* - 50
NE050	50	4,1	810	220	5	7	25* - 50
NE055	55	4,2	895	250	5	7	25* - 50
NE060	60	4,2	975	280	5	7	25* - 50
NE063	63	4,3	1050	300	4	7	25* - 50
NE070	70	4,6	1200	325	4	7	25* - 50
NE075	75	4,8	1390	345	4	7	25* - 50
NE080	80	5,2	1580	360	3	7	25* - 50
NE090	90	5,5	1850	425	3	7	25* - 50
NE100	100	6	2200	480	3	7	25* - 50
NE110	110	6,1	2530	525	3	6	25*
NE120	120	6,2	2800	670	2	6	25*

Product ID: 14050

Source URL: <https://alfaflex.com/en/products/10000/14000/opal-1>