

Alfaspir N



Very flexible pvc hose smooth on the inside, to used as a protection hose for cables, but also suitable for ventilation.

Construction: Grey self-extinguishing pvc with an embedded white hard pvc spiral. (anti shock)

Temperature: -5°C to +60°C

Applications

Ventilation, draining without pressure, suction of non-abrasives materials

| Reference | Diameter (mm) | Wall thickness (mm) | Weight (g/m) | Bending radius (mm) | Vacuum (mH2O) | Coil length (m) |
|-----------|---------------|---------------------|--------------|---------------------|---------------|-----------------|
| EOG020 | 20 | 0,75 | 125 | 30 | 5 | 50 |
| EOG025 | 25 | 0,75 | 150 | 30 | 5 | 50 |
| EOG030 | 30 | 0,8 | 190 | 40 | 5 | 50 |
| EOG032 | 32 | 0,8 | 205 | 40 | 4,5 | 50 |
| EOG035 | 35 | 0,8 | 235 | 45 | 4,5 | 50 |
| EOG038 | 38 | 0,8 | 255 | 45 | 4,5 | 50 |
| EOG040 | 40 | 0,85 | 290 | 50 | 4 | 50 |
| EOG045 | 45 | 0,85 | 360 | 60 | 4 | 50 |
| EOG050 | 50 | 0,85 | 440 | 60 | 4 | 50 |
| EOG055 | 55 | 0,85 | 550 | 65 | 4 | 50 |
| EOG060 | 60 | 0,85 | 500 | 70 | 4 | 50 |
| EOG063 | 63 | 0,9 | 535 | 75 | 4 | 50 |
| EOG070 | 70 | 0,9 | 590 | 85 | 4 | 50 |
| EOG075 | 75 | 0,9 | 640 | 95 | 4 | 50 |
| EOG080 | 80 | 0,95 | 740 | 115 | 4 | 50 |
| EOG090 | 90 | 0,95 | 850 | 130 | 4 | 50 |
| EOG100 | 100 | 1 | 970 | 140 | 4 | 30 |
| EOG110 | 110 | 1 | 1050 | 150 | 4 | 30 |
| EOG120 | 120 | 1 | 1150 | 160 | 4 | 30 |
| EOG125 | 125 | 1 | 1240 | 165 | 4 | 30 |
| EOG130 | 130 | 1,1 | 1650 | 170 | 3,5 | 30 |
| EOG140 | 140 | 1,1 | 1440 | 180 | 3,5 | 30 |
| EOG150 | 150 | 1,1 | 1700 | 180 | 3,5 | 20 |
| EOG160 | 160 | 1,15 | 1900 | 200 | 3,5 | 20 |
| EOG170 | 170 | 1,15 | 2350 | 245 | 3 | 20 |
| EOG180 | 180 | 1,15 | 2200 | 290 | 3 | 20 |
| EOG200 | 200 | 1,2 | 2600 | 380 | 2,5 | 20 |
| EOG250 | 250 | 1,2 | 3600 | 470 | 2,5 | 10 |
| EOG300 | 300 | 1,3 | 4500 | 560 | 2,5 | 10 |