

Alfaspir PU



Very flexible polyurethane (PU) hose with a smooth inside, suitable for the suction of abrasive materials and resistant to hydrolysis and bacteria.

Temperature: -20°C to +80°C

Construction: transparent PU with embedded a white hard pvc helix.

Remark: On demand also available in black

Applications

woodchips, grass, leaves, ...

Reference	Diameter (mm)	Wall thickness (mm)	Spiral (mm)	Weight (g/m)	Bending radius (mm)	Vacuum (mH20)	Coil length (m)
EOPU030	30	0,5	2,4	165	70	3	25
EOPU035	35	0,5	2,4	200	90	3	25
EOPU040	40	0,5	2,5	230	100	3	25
EOPU050	50	0,5	3	340	140	2,5	25
EOPU060	60	0,5	3,3	425	160	2,5	25
EOPU070	70	0,5	3,3	500	190	2,5	25
EOPU075	75	0,5	3,4	550	200	2,5	25
EOPU080	80	0,6	3,5	590	220	2,5	25
EOPU090	90	0,6	4,2	670	260	2	25
EOPU100	100	0,6	4,3	750	280	2	25
EOPU110	110	0,6	4,5	850	300	2	25
EOPU120	120	0,6	5	930	320	2	25
EOPU125	125	0,7	5	1050	340	2	25
EOPU140	140	0,7	5,2	1250	360	2	25
EOPU150	150	0,7	5,6	1350	400	2	10 - 25
EOPU160	160	0,8	5,8	1450	440	2	10 - 25
EOPU180	180	0,8	6	1750	500	2	10 - 25
EOPU200	200	0,8	6,1	1950	560	2	10 - 25

Product ID: 14150

Source URL: <https://alfaflex.com/en/products/10000/14000/alfaspir-pu-0>