


SBR



SBR rubber sheets with or without ply are very suitable for divers applications with the exception of chemicals and hydrocarbons. Both surfaces are smooth.

Temperature: -10°C to +70°C

- Hardness : 65 °Shore +/-5
- Density: 1,6 g/cm³
- Tensile strength : 3 MPa
- Elasticity at rupture: 200 %

| Thickness (mm) | Width (m) | Length (m) | Ref no ply | Ref 1 ply | Ref 2 ply |
|----------------|-----------|------------|------------|-----------|-----------|
| 1 | 1,40 | 10,00 | RP0100 | - | - |
| 1,5 | 1,40 | 10,00 | RP01500 | - | - |
| 2 | 1,40 | 10,00 | RP0200 | RP0201 | - |
| 3 | 1,40 | 10,00 | RP0300 | RP0301 | RP0302 |
| 4 | 1,40 | 10,00 | RP0400 | RP0401 | RP0402 |
| 5 | 1,40 | 10,00 | RP0500 | RP0501 | RP0502 |
| 6 | 1,40 | 10,00 | RP0600 | RP0601 | RP0602 |
| 8 | 1,40 | 5,00 | RP0800 | RP0801 | RP0802 |
| 10 | 1,40 | 5,00 | RP1000 | RP1001 | RP1002 |
| 15 | 1,40 | 5,00 | RP1500 | - | RP1502 |
| 20 | 1,00 | 1,00 | RP2000 | - | - |
| 30 | 1,00 | 1,00 | RP3000 | - | - |
| 40 | 1,00 | 1,00 | RP4000 | - | - |
| 50 | 1,00 | 1,00 | RP5000 | - | - |

Product ID: 31010

Source URL: <https://alfaflex.com/en/products/30000/31000/sbr-0>