

## AX Dry Cement S&D



Antistatic NR/SBR suction and delivery hose for conveying and handling dry abrasive bulk materials at low pressure (10 bar). Suitable for applications in silos and tank trucks.

Temperature: -40°C to +70°C

- **Tube:** black smooth anti static NR/SBR rubber
- **Reinforcement:** high tenacity textile yarn and embedded steel helix
- **Cover:** black antistatic NR/SBR rubber with cloth impression, abrasion and weathering resistant

**Abrasion loss of the tube:** rubber compound according to DIN 53516 70±5 mm<sup>3</sup>

**Remark:** Other diameters, pressure ratings and inner tube rubber quality (higher abrasion resistance, light coloured para rubber) available on request.

### Applications

cement, sand, gravel, chalk, lime, ...

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Vacuum (mH20)	Bending Radius (mm)	Coil length (m)
TBX050	51 x 65	1.920	10	30	0,9	300	40 - 61
TBX065	65 x 79	2.430	10	30	0,9	380	40 - 61
TBX075	76 x 92	3.280	10	30	0,9	450	40 - 61
TBX090	90 x 110	3.800	10	30	0,9	540	40 - 61
TBX100	102 x 118	4.800	10	30	0,9	610	40 - 61
TBX110	110 x 129	5.600	10	30	0,8	660	40 - 61
TBX115	115 x 135	5.800	10	30	0,8	700	40 - 61
TBX125	127 x 147	6.800	10	30	0,8	760	40 - 61
TBX125	152 x 174	11.000	10	30	0,8	920	40 - 61
TBX200	203 x 229	16.300	10	30	0,7	1220	40

Product ID: 40110

Source URL: <https://alfaflex.com/en/products/40000/40100/ax-dry-cement-sd-0>