

AX UPE S&D EN12115



Suction and delivery hose of a wide range of aggressive chemicals, petroleums, acids, bases, ketons, esters, aromatic, aliphatic and chlorinated hydrocarbons, even at high temperatures. Also suitable for animal or vegetable foodstuffs and alcoholic drinks.

Temperature: -30°C to +100°C

- **Tube:** smooth translucent UHMWPE(*) rubber (also available in conductive black), FDA approved
- **Reinforcement:** high strength synthetic cord, embedded steel helix wire and anti-static copper wire to facilitate the electrical connection
- **Cover:** black, anti-static EPDM with cloth impression ($R < 10^6 \Omega/m$) weathering, ozone resistant

Norm: EN 12115

Applications

Depending on temperature and concentration, suitable for 95% of the chemicals.

(*) Ultra High Molecular Weight Poly-Ethylene

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Bending radius (mm)	Coil length (m)
	32 x 43	1.370	10	40	190	40
	38 x 49	1.470	10	40	230	40
	50 x 63	2.090	10	40	310	40
	63 x 77	2.950	10	40	380	40
	75 x 89	3.440	10	40	460	40
	100 x 115	4.570	10	40	610	40

Product ID: 40203

Source URL: <https://alfaflex.com/en/products/40000/40200/ax-upe-sd-en12115-0>