


AX NBR S&D EN 12115



Mandrel built suction and delivery hose for conveying domestic oils and fuels. The maximum vacuum capacity of the hose is 80%.

Temperature: -30°C to +100°C

- **Inner tube:** smooth black NBR
- **Reinforcements:** high tensile textile inserts, steel helix and antistatic copper wire
- **Cover:** black smooth NBR with cloth finish, resistant to oil

Norm: EN12115

Applications

tank trucks, petrol stations, ...

| Ref | Diameter (mm) | Weight (g/m) | WP (bar) | BP (bar) | Bending Radius (mm) | Ref |
|-----|---------------|--------------|----------|----------|---------------------|-----|
| | 30 x 40 | 970 | 16 | 48 | 200 | |
| | 40 x 50 | 1.790 | 16 | 48 | 250 | |
| | 50 x 64 | 2.330 | 16 | 48 | 300 | |
| | 60 x 74 | 2.710 | 16 | 48 | 360 | |
| | 70 x 84 | 3.130 | 16 | 48 | 420 | |
| | 75 x 89 | 3.330 | 16 | 48 | 500 | |
| | 80 x 94 | 3.530 | 16 | 48 | 600 | |
| | 100 x 116 | 4.940 | 12 | 36 | 1.000 | |

Product ID: 40618

Source URL: <https://alfaflex.com/en/products/40000/40600/ax-nbr-sd-en-12115-0>