

## AX Fibreglass 20 bar



Mandrel built glassfibre covered hose resisting to steel splashes.

Temperature: -40°C to +130°C

- **Tube:** black smooth EPDM rubber
- **Reinforcement:** high tensile textile plies
- **Cover:** black EPDM rubber covered with vulcanized glass fibre ply, resistant to radiant heat

### Applications

Delivery of water cooling in foundries, glass, steel or iron industry. For situations where hoses are exposed to sprinkles of red hot material.

Ref	Diameter (mm)	Weight (g/m)	WP (bar)	BP (bar)	Coil length (m)
FBR010	10 x 20	300	20	60	40
FBR013	13 x 24	450	20	60	40
FBR016	16 x 27	500	20	60	40
FBR019	19 x 32	600	20	60	40
FBR025	25 x 39	900	20	60	40
FBR030	30 x 42	800	20	60	40
FBR032	32 x 48	1.300	20	60	40
FBR038	38 x 55	1.700	20	60	40
FBR040	40 x 59	1.900	20	60	40
FBR050	51 x 71	2.500	20	60	40
FBR065	65 x 86	3.250	20	60	40

Product ID: 40940

Source URL: <https://alfaflex.com/en/products/40000/40900/ax-fibreglass-20-bar-0>