

Firefighting Hose



Lay flat firefighting hose with an excellent price-to-quality ratio. Very suitable for construction or industry

Composition:

Temperature: -30°C to +60°C

- **Tissue:** diagonal woven high tensile yarn, 100% polyester
- **Tube:** EPDM, synthetic rubber

Characteristics:

- Delivery hose, very flexible, light and easy to use
- Resistant to mildew with a minimal maintenance

Available in: white or with a red polyurethane* coating

* improves abrasion resistance

Applications

Industry, civil construction, cleaning and maintenance, agriculture, pumps, transport of fluids, ...

Diameter (mm)	Diameter (inch)	Weight (g/m)	Working Pressure (bar)	Burst Pressure (bar)	Ref White	Ref Red	Coil length (m)
25	1"	105	14	42	PO025W	PO025R	20 - 40
32	1"1/4		14	42	PO032W	PO032R	20 - 40
38	1"1/2	180	14	42	PO038W	PO038R	20 - 40
42	1"5/8		14	42	PO040W	PO040R	20 - 40
45	1"3/4	200	14	42	PO045W	PO045R	20 - 40
50	2"	230	14	42	PO050W	PO050R	20 - 40
63	2"1/2	300	12	36	PO065W	PO065R	20 - 40
70	2"3/4		12	36	PO070W	PO070R	20 - 40
75	3"	390	12	36	PO075W	PO075R	20 - 40
90	3"1/2	500	10	30	PO090W	PO090R	20 - 40
100	4"	585	10	30	PO100W	PO100R	20 - 40
110	4"1/2	665	10	30	PO110W	PO110R	20 - 40
150	6"	930	8	24	PO150W	PO150R	20 - 40



☐☐☐ **Firefighting Hose**
www.alfaflex.com

Source URL: <https://alfaflex.com/en/products/50000/brandweerslang-0>